

PK-10SP Packing Instructions (Canada)

Shipper must ensure compatibility with all packaging materials and follow all appropriate transport regulations. For air shipment of liquids, containers must meet pressure, secondary closure and leak-proof liner requirements (**See IATA DGR Section 5 / ICAO TI Section 4**). Deviations from any part of this instruction may void the UN certification. Please consult 49 CFR for United States record retention requirement. If further information is required, contact ICC The Compliance Center Inc at 1-888-442-9628.

Packaging Components

Item	Description	Qty
BX-10SP	Outer box (12" x 12" x 16 ¼")	1
BI-BSS10	Liner Bag (43" x 48")	1

Packaging Components required to complete this assembly supplied separately

AB-VERM4	Vermiculite or equivalent absorbent and/or cushioning material. Use sufficient quantity of absorbent to absorb the entire liquid contents. All void space must be filled.
PA-MSST1	3M # 305 48mm clear tape or equivalent



Important Information

Each assembled package must not exceed a gross weight of	15.8kg/34.76lb
The combined gross weight of inner containers must not exceed	10.7kg/23.5lb
Minimum Cushioning Distance Top/Bottom	2"
Minimum Cushioning Distance Side	1 ½"

Assembly:

- Set up outer box by folding bottom flaps. Seal center seam with two (2) strips of 48mm wide, 3M #305 clear packing tape **or** two (2) strips of 3" wide, Central Brand #260 reinforced paper tape **or** equivalent. Extend tape beyond edge by at least 2".
- Line inside bottom and walls of box with liner bag (Figure 1).
- Do not completely fill each inner container with liquid. Leave sufficient space in each container for expansion. Tighten cap to specifications.
- Evenly spread a 2" layer of absorbent/cushioning in bottom of box/bag assembly. Place inner container(s) in box over 2" layer of absorbent/cushioning. Each container must be a minimum of 1 ½" apart from other containers and from the inside walls of the box (Figure 2).
- Fill all void space with absorbent/cushioning. Maintain a minimum 2" layer of absorbent/cushioning over the top of each container.
- Fold and seal top portion of liner bag (Figure 3).
- Fold top box flaps and seal center seam as described above in step 1 (Figure 4).
- Mark and label each package in accordance with the appropriate regulations. At least one (1) set of UN markings and two (2) sets of orientation arrows must be show on each package.

Figure 1



Figure 2



Figure 3



Figure 4

