

PK- LITH0902 (Large) Packing Instructions

Shipper must ensure compatibility with all packaging materials and follow all appropriate transport regulations. For air shipment of liquids, containers must meet pressure, secondary closure and leak-proof liner requirements (**See IATA DGR Section 5 / ICAO TI Section 4**). Deviations from any part of this instruction may void the UN certification. Please consult 49 CFR for United States record retention requirement. If further information is required, contact ICC The Compliance Center Inc at 1-888-442-9628.

Packing Components

Item	Description	Qty.
BX-19 SP	Outer Box 11" X 11" X 11 1/2"	1
BI-BSS9	26" x 36" Liner Bag	1
AB-SSBP01	3/16 " Bubble Pouch, 7" x 11 1/2"	1

Packing Components completing this assembly supplied separately

AB-PEABD01	12 Cubic feet, white biodegradable peanuts. Use sufficient quantity for cushioning distance.
AB-SSBP01	Use for individual battery wrap and cushioning
PA-MSST1	3M # 305 48mm clear tape or equivalent

Important Information

Each assembled package must not exceed a gross weight of	10.14kg/22.3lb
The combined gross weight of inner containers must not exceed	8.0kg/17.8
Minimum cushioning distance for top/bottom	1 1/2"
Minimum cushioning distance sides	1 1/8"

Assembly

1. Fold in bottom flaps. Seal center seam with (2) strip of 48mm wide, 3M #305 clear packing tape or equivalent. Extend tape beyond each edge by at least 2".
2. Line the inside bottom and inside walls of box with liner bag (Figure 2).
3. Evenly spread a minimum layer of 1 1/2" of white biodegradable peanuts/cushioning in bottom of box. Place battery in pouch and seal.
4. Fill all void space with cushioning. Maintain a minimum layer of 1 1/2" top, sides and components (Figure 3).
5. Fold and seal top portion of liner bag (Figure 4).
6. Fold top flaps of box and seal center seam as described above in step 1 (See figure 5)
7. Mark and label each package in accordance with the appropriate regulations. At least one (1) set of UN markings and two (2) sets of orientation arrows must be shown on each package.

Figure 1.



Figure 2.



Figure 3.




Figure 4.



Figure 5.

