

Packing Instructions for kit number

PK-MT132



4G/Y4.0/S/**

USA/M5377

** Indicates year of production

IMPORTANT WARNING! This packing instruction details correct assembly of this packaging design. Deviation may result in non-compliance and voiding the certification. ICC The Compliance Center Inc. is not responsible for any packagings using substitute components or assembled incorrectly. If further information is required, please contact ICC The Compliance Center Inc. at 1-800-767-7231.

SHIPPER'S RESPONSIBILITY includes ensuring that all inner containers, closures, liners, cushioning and (absorbent when applicable) will not react dangerously with the contents, and for AIR SHIPMENT, that inner containers for liquids are capable of meeting a minimum internal pressure differential of 95kpa without leakage. Some volatile liquids may require a higher test pressure. See ICAO Technical Instruction Part 3, Chapter 1, Sec 1.1.6.1 or IATA DGR 5.0.2.9.

Figure 1.

PACKAGING COMPONENTS: (See Figure 1).

<u>Item number</u>	<u>Description</u>	<u>Quantity</u>
1. BX-26CA	Outer box	One
2. IN-26CA2	Corrugated Insert	One
3. MT-FQUA	Steel F-Style Quart Can (tested to 95kPa with MS-CAP)	Two
4. MS-CAP	Steel Cap with Coated-Paper Seal	Two

Other items required to complete this packaging assembly supplied separately:

- MS-ST-1 3M #305, 48mm wide clear packing tape or equivalent



**Do not exceed a maximum gross weight of 4.0 kilograms (8.8 pounds) as marked on the box.
Maximum Specific Gravity of liquid 1.8**

PACKAGING ASSEMBLY INSTRUCTIONS:

1. Set up outer box by folding in bottom flaps. Seal center seam with one (1) strip of 48mm wide, 3M #305 clear packing tape or equivalent extending beyond each edge by at least 2" (inches).
2. Do not completely fill inner containers with liquid. Leave sufficient space in each container for expansion. (See 49 CFR 173.24 (h) or IATA 5.0.2.8). **Tightly secure each cap to prevent leaking.**
3. Place one assembled can in an upright position in box. (See Figure 3).
4. Assemble insert and place it in box beside can. (See Figures 2 and 3).
5. Place other can in an upright position on other side of insert in box. (See Figure 4).
6. Fold top box-flaps and seal center seam as described above in step one. (See Figure 5).
7. Mark and label each package in accordance with the appropriate regulations. At least one (1) set of UN markings and two (2) orientation arrows must be shown on each package.

Figure 2.



Figure 3.



Figure 4.



Figure 5.

