

SDS Workflow



MSDS INFORMATION

Product Identifier: Adhesive Spray UN 1459
 Product use: Annual webbing adhesive for screen printing applications.
 Supplier name and address:
COMPANY ABC
 3641 36th Street
 Big City, New York
 United States
 11106
 718-901-8272

Emergency Telephone #: Chemical (Day or Night) 888-555-5555
 (For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)
 This MSDS complies with 29 CFR 1910.1200 (Hazard Communication Standard) and WHMIS regulations.
 IMPORTANT: Read this MSDS before handling and disposing of this product. For the information on to use
 customers, and users of this product.

2-Propenone
 Dimethyl ether
 Heptane

Sara 313 Listed Chemicals
 Heptane CAS # 100-56-3 % (weight) 15-40
 Chemical Family: Hydrocarbon blend in pressurized aerosol cans. CAS No.: Mixture.

*Note: The TLV listed above for Dimethyl ether is recommended by the American Industrial Hygiene Association (AIHA).

*****POTENTIAL HEALTH EFFECTS*****
Target organs: Eyes, skin, respiratory system, central nervous system
Signs and symptoms of short-term (acute) exposure:
 Breathing vapors or mist may be harmful. Irritation may cause irritation to the nose, throat, and respiratory system. Symptoms of overexposure may include: dizziness, disorientation, fatigue, nausea, headache and other central nervous system effects. In confined or poorly ventilated areas where the vapor concentration is very high, product may act as an asphyxiant and cause increased breathing and other symptoms, including: nausea, vomiting, respiratory collapse and death.
Skin contact: Skin contact may cause irritation. Symptoms may include stinging, a burning sensation, redness and swelling. Symptoms of frostbite may be experienced including numbness, tingling and itching.
Eye contact: Direct eye contact may cause severe irritation and corneal damage. Product may freeze the eye and cause eye damage.
Ingestion: Swallowing may cause irritation to the mouth, throat and stomach. Symptoms may include dizziness, disorientation, fatigue, nausea, headache and other central nervous system effects.
Effects of long-term (chronic) exposure: Prolonged or repeated skin exposure may cause redness, burning, drying and cracking of the skin or irritation. Prolonged overexposure may cause peripheral nervous system damage (numbness).
Other important hazards: CNS depression may result from exposure. Ingestion may cause aspiration of the chemical into the lungs. Aspiration can result in life threatening lung injury.

NON-COMPLIANT MSDS

ICC prepares a compliant 16-part SDS

Compliant SDS translation to more than 41 languages

SAMPLE COATING ADDITIVE
 Prepared by: August 20, 2012

ICC The Compliance Center Inc.
 2150 Green Drive
 Niagara Falls, NY, U.S.A.
 14303
 Information Telephone #: (716) 263-6600; (800) 442-0628 (9 AM to 6 PM, EST, Monday to Friday)
 24-Hr. Emergency Tdd: Chemistry (Day or Night) 800-242-6000

SAFETY DATA SHEET

SECTION 1—IDENTIFICATION
 Product Identifier used on the label: SAMPLE COATING ADDITIVE
 Other means of identification (e.g. Product code(s)): Polymer solution
 Chemical Family: Mixture of Aromatic Hydrocarbons, Ketones, Polymers
 Recommended use of the chemical and restrictions on use: Polymer solution • Additive for coatings. Professional use only.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:
ICC The Compliance Center Inc.
 2150 Green Drive
 Niagara Falls, NY, U.S.A.
 14303
 Information Telephone #: (716) 263-6600; (800) 442-0628 (9 AM to 6 PM, EST, Monday to Friday)
 24-Hr. Emergency Tdd: Chemistry (Day or Night) 800-242-6000

SECTION 2—HAZARD IDENTIFICATION
 Classification of the chemical:
 Clear light yellow viscous liquid. Aromatic solvent other.
 Most important hazards: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazard 2012). Hazardous classification:
 Flammable liquid - Category 3
 Skin irritation - Category 2
 Reproductive toxicity - Category 2
 Specific target organ toxicity - single exposure - Category 3
 Specific target organ toxicity - repeated exposure - Category 2

Label elements:
 Signal Word:
 Warning:
 (Hazard statement)
 Flammable liquid and vapor.
 Causes skin irritation.
 Suspected of damaging the unborn child.
 May cause drowsiness and dizziness.
 May cause damage to the nervous system through prolonged or repeated exposure.
 Precautionary statement(s):
 Obtain special instructions before use.
 Do not breathe dust and all other precautions have been read and understood.
 Keep away from heat, sparks and open flame. No smoking.
 Keep container tightly closed.
 Ground/Bond container and receiving equipment.
 Use explosion proof venting equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe vapor.
 Wash hands thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only containers in a well ventilated area.

FULLY COMPLIANT SDS

ICC prepares your compliant label text

ICC does the translation

PRODUCT IDENTIFIER

WARNING:
 Flammable solid. Dust can readily ignite when suspended in air. May cause lung irritation and allergic reaction. Causes skin and eye irritation. Harmful if swallowed.

PRECAUTIONS:
 Wear protective equipment for dusty conditions, including a NIOSH/MSHA approved respirator. Avoid breathing dust. Avoid contact with eyes, skin and clothing. Avoid dust cloud formation. Keep away from heat, sparks and flame. Store in a cool, well ventilated area, away from incompatible.

FIRST AID:
 If inhaled, remove victim to fresh air. If breathing stopped, begin artificial respiration. Call physician. If in contact with eyes, immediately flush eyes with running water for at least 20 minutes. Call physician immediately. For skin contact wash with soap and water for at least 15-20 minutes while removing contaminated clothing. Call physician immediately. If ingested, do not induce vomiting. Guard against aspiration into lungs. Obtain medical attention immediately.

AVERTISSEMENT:
 Solide inflammable. La poussière en suspension dans l'air peut facilement s'enflammer. Peut irriter les yeux et la peau et causer une réaction allergique. Irrite la peau et les yeux. Nocif si avalé.

PRÉCAUTIONS:
 Si les conditions sont poussiéreuses, porter un équipement de protection, incluant un respirateur approuvé par NIOSH/MSHA. Éviter de respirer les poussières. Éviter tout contact avec les yeux, la peau et les vêtements. Éviter la formation de nuages de poussière. Tenir à l'écart des étincelles, des flammes et de la chaleur. Entreposer dans un endroit frais, bien ventilé, à l'écart des matières incompatibles.

PREMIERS SOINS:
 Si inhalé, transporter la victime à l'air frais. En cas d'arrêt respiratoire, pratiquer la respiration artificielle. Appeler un médecin. En cas de contact avec les yeux, rincer immédiatement les yeux avec l'eau courante pendant au moins 20 minutes. Appeler immédiatement un médecin. En cas de contact avec la peau, laver avec du savon et de l'eau, pendant au moins 15-20 minutes, tout en retirant les vêtements contaminés. Appeler immédiatement un médecin en cas d'ingestion, ne pas faire vomir. Veiller à ce que le produit ne soit pas aspiré. Obtenir des soins médicaux immédiats.

Refer To Material Safety Data Sheet for further information.
 Pour plus de renseignements, consulter la fiche signalétique.

COMPANY NAME
 ADDRESS
 CITY, PROVINCE POSTAL CODE

Fully compliant labels

WHMIS

GHS (OSHA Hazcom 2012)

Calcium Nitrate

Calcium Nitrate
 UN1454

5.1

\$50.00 34234 20 KGS

TOLUENE / TOLUENO

TOLUENE / TOLUENO
 UN1294

FLAMMABLE LIQUID
 3

356 lbs