

## PK- LITH0601 Exempt - Packing Instructions

Shipper must ensure compatibility with all packaging materials and follow all appropriate transport regulations. Please consult 49 CFR for United States record retention requirement. If further information is required, contact ICC The Compliance Center Inc at 1-888-442-9628.

### Packaging Components

Item	Description	Qty
BX-106	11 ¼" x 6 5/8" x 3 ½"	1
AB-SSBP01	Anti-static bubble wrap pouch 7" x 8 ½"	1
	or	
AB-SSBP03	Anti-static bubble wrap pouch 7" X 11 ½"	1
LB-USI6603	Lithium battery label 4.5" x 5"	1

### Important Information:

The lithium content anode of each cell, when fully charged ,is not more than 5 grams
Use cushioning to fill void space
Tape for closure on open edges is recommended

### Box Assembly:

1. Fold in side bottom back flaps. (Figure 1)
2. Fold in bottom panel both sides and upper panel both sides. Push down so the top side panels overlap the bottom side panels. (Figures 2 & 3)
3. Fold in front panels.(Figure 4)
4. Wrap battery in pouch. Make sure battery connections are covered.
5. Fill all the void space with cushioning.
6. Bring front panel up to close box. Orientation arrow facing up. Tuck in flap.(Figure 5)
7. Push small tab on top into slot on top of front panel above orientation arrow.(Figure 6)
8. Label box accordingly.

Figure 1



Figure 2



Figure 3



Figure 4



Figure 5



Figure 6



Final Assembly

