

## PK- MT131 Packing Instructions

Shipper must ensure compatibility with all packaging materials and follow all appropriate transport regulations. For air shipment of liquids, containers must meet pressure, secondary closure and leak-proof liner requirements (**See IATA DGR Section 5 / ICAO TI Section 4 / US 49 CFR 173.27**). Deviations from any part of this instruction may void the UN certification. Please consult 49 CFR for United States record retention requirement. If further information is required, contact ICC Compliance Center at 1-888-442-9628.

### Packing Components

Item	Description	Qty.
BX-26CA	Outer box	1
IN-26CA1	Insert for F-Style quart box	1
MT-FQUA	F-Style Quart Can	1
CP-FCHILDPR	Cap for F-Style Quart Can	

### Packaging components completing this assembly supplied separately

PA-MSST4	3M # 375 48mm clear tape
----------	--------------------------

### Important Information

Each assembled package must not exceed a gross weight of	4.3kg/9.4lb
Maximum Specific Gravity of Liquids	1.8
Cap closure past contact with gasket	¼ turn or 30 in. lbs



### Assembly

- Set up outer box by folding in bottom flaps. Seal center seam with one (1) strip of 3M #375,48mm,clear tape. Extend the tape edge beyond each edge by at least 2".
- Assemble insert with top and bottom flaps folded out (Figure 2 and 3)
- Do not completely fill inner container with liquid. Allow sufficient ullage for expansion. Tighten cap to specifications.
- Place assembled can in insert/box assembly in an upright position. Fold top box-flaps over and seal center seam as described above in step one (Figure 4).
- Mark and label each package in accordance with the appropriate regulations. At least one (1) set of UN markings and two (2) orientation arrows must be shown on each package.

Figure 2.



Figure 3.



Figure 4.



**DATE:** MAY 9, 2018

**TO:** Valued ICC Customers

**RE:** Changes to BX-26CA

Dear Valued Customer,

In an effort to continuously improve the quality and performance of our UN packaging, we occasionally must make changes to the specifications and usage instructions. This notice is to inform you that the following changes have been made to **BX-26CA (PK-MT-131 and PK-MT132)**.

1. The clear tape required for closure of this packaging has changed from 3M #305 48mm wide clear tape to 3M #375 48mm wide clear tape. This change to a stronger tape caused the box to perform better in drop tests, resulting in a more secure packaging.

If you have any questions or concerns, please contact our customer relations center in the US at 888-442-9628 or in Canada at 888-977-4834.

Thank you,

Michael S. Zendano  
Packaging Specialist