

PK-N2GALFCN/PKN2GALFN Packing Instructions

Shipper must ensure compatibility with all packaging materials and follow all appropriate transport regulations. For air shipment of liquids, containers must meet pressure, secondary closure and leak-proof liner requirements (**See IATA DGR Section 5 / ICAO TI Section 4 / US 49 CFR 173.27**). Deviations from any part of this instruction may void the UN certification. Please consult 49 CFR for United States record retention requirement. If further information is required, contact ICC Compliance Center at 1-888-442-9628.

Packing Components

Item	Description	Qty.
BX-86N	Outer Box	1
MT-USPCGALH	Gallon Paint Can with Lid	2
FO-KFGN	Gallon PE foam pad	4
RL-CJ7	Gallon Sealing Ring	2

Packing components completing this assembly supplied separately

PA-MSST4	3M #375, 48mm wide clear packing tape
----------	---------------------------------------

Important Information

Each assembled package must not exceed a gross weight of	18kg/39.6lb
Maximum Specific Gravity of Liquids	2.18
Lid closure is to be even with top of can	

Assembly

Set up the corrugated box. Flip the box upside down and fold in the minor flaps (inner flaps), and then fold in the major flaps (outer flaps). Apply 1 strip of 2" wide 3M #375 tape lengthwise over the center seam extending a minimum of 2.0" over the edges.

- Place one of the foam pads on the bottom of the corrugated box with the cutout pad facing upwards (Figure 1).
- Fill the inner packaging to the proper weight and volume, be sure not to overfill the container. (Allow sufficient ullage for liquid expansion)
- Using a lid applicator, secure lid completely and evenly until it is seated flush with the top of the can.
- Secure Ringlok completely and evenly on each can/lid assembly. Make sure ring snaps completely in place (see instructions on page 2). Place can/ring assembly in an upright position in box over foam-pad.
- Place the other foam-pad with cutout pointing down over top of can/ring assembly (Figure 2).
- Repeat steps 2-6 with the remaining paint can.
- Secure the top of the box closed. Flip the box upside down and fold in the minor flaps (inner flaps), and then fold in the major flaps (outer flaps). Apply 1 strip of 2" wide 3M #375 tape lengthwise over the center seam extending a minimum of 2.0" over the edges (Figure 3).
- Mark and label each package in accordance with the appropriate regulations. At least one (1) set of UN markings and two (2) orientation arrows must be shown on each package.

(Figure 1)



(Figure 2)



(Figure 3)



Ringlok® Instructions (RL-CJ7 & RL-CJ8)

ASSEMBLY



- 1 Place the Ringlok® on the paint can.
- 2 Using the palms of both hands, concentrate on one end of the ring and press firmly. (This will result in the ring hooking the outer rim of can.)



- 3 Using palms of both hands, continue to "firmly" press the ring into place and work both hands around the perimeter, until the ring is completely applied.
- 4 The ring is properly applied when the ring hooks below the can's rim completely around the perimeter.



REMOVAL

- 1 Pry the ring in an upward position using two thumbs concentrated on one area until the ring releases from the can's rim.



USA

Cleveland
Niagara Falls
Houston

USA Customer Service
Tel: 888-442-9628

CANADA

Edmonton
Montreal
Toronto
Vancouver

Canada Customer Service
Tel: 888-977-4834

www.thecompliancecenter.com