

PK- N4QT Packing Instructions

Shipper must ensure compatibility with all packaging materials and follow all appropriate transport regulations. For air shipment of liquids, containers must meet pressure, secondary closure and leak-proof liner requirements (**See IATA DGR Section 5 / ICAO TI Section 4 / US 49 CFR 173.27**). Deviations from any part of this instruction may void the UN certification. Please consult 49 CFR for United States record retention requirement. If further information is required, contact ICC Compliance Center at 1-888-442-9628.

Packing Components

Item	Description	Qty.
BX-32	Die-cut outer box	1
MT-PCCLIPS	Metal Paint Can Clips (6 per can)	24

Packaging components completing this assembly supplied separately

PA-MSST4	3M # 375 48mm clear tape
----------	--------------------------

Important Information

Each assembled package must not exceed a gross weight of	10.3kg/22.7lb
Maximum Specific Gravity of Liquids	1.6
Lid closure is to be even with top of can	



Figure 1.

Assembly

1. Fold in bottom flap. Make sure flap-ends point into box creating four individual cells and seal the center seam of box with two (2) strips of 3M #375,48mm clear tape. Extend tape beyond each edge by at least 2". (Figures 2, 3 and 4). The tape strips run together overlapping side by side by .5".
2. Do not completely fill each can with liquid. Allow sufficient ullage for liquid expansion. Using a paint can closer, secure lid evenly on can.
3. Secure six (6) metal clips spaced evenly apart or one (1) Ringlok on can/lid assembly. Make sure Ringlok snaps completely and evenly in place (see page 2). For metal clips, make sure "double hook" end of clips grip on outer rim of can.
4. Place one can assembly in an upright position in each box cell (Figure5).
5. Fold box flaps with flap-ends separating all cans. Seal center seam as described above (Figures 6 and 7).
6. Mark and label each package in accordance with the appropriate regulations. At least one (1) set of UN markings and two (2) orientation arrows must be shown on each package.

Figure 2.



Figure 3.




Figure 4.



Figure 5.



Figure 6.



Figure 7.



Dear Valued Customer,

In an effort to continuously improve the quality and performance of our UN packaging, we occasionally must make changes to the specifications and usage instructions. This notice is to inform you that the following changes have been made to **BX-32 (Including PK-N4QT, PK-N4QTC, and PK-N4PTC.)**

1. The clear tape required for closure of this packaging has changed from 3M #305 48mm wide clear tape to 3M #375 48mm wide clear tape. This change to a stronger tape caused the box to perform better in drop tests, resulting in a more secure packaging.
2. The amount of clips that attach to each can is changing from 4 to 6.

If you have any questions or concerns, please contact our customer relations center in the US at 888-442-9628 or in Canada at 888-977-4834.

Thank you,

Michael S. Zendano
Packaging Specialist



Ringlok® Instructions (RL-CJ7 & RL-CJ8)

ASSEMBLY



- 1 Place the Ringlok® on the paint can.
- 2 Using the palms of both hands, concentrate on one end of the ring and press firmly. (This will result in the ring hooking the outer rim of can.)
- 3 Using palms of both hands, continue to "firmly" press the ring into place and work both hands around the perimeter, until the ring is completely applied.
- 4 The ring is properly applied when the ring hooks below the can's rim completely around the perimeter.



REMOVAL



- 1 Pry the ring in an upward position using two thumbs concentrated on one area until the ring releases from the can's rim.



USA

Cleveland
Naperville, IL
Houston

USA Customer Service
Toll 888-442-9628

CANADA

Edmonton
Montreal
Toronto
Vancouver

Canada Customer Service
Toll 888-977-4834

www.thecompliancecenter.com