

SKOLNIK

TESTING PERFORMED BY SKOLNIK INDUSTRIES, INC.
 TESTING LAB - AKA: "SDCC"
 4900 South Kilbourn Avenue Chicago, Illinois 60632

ID NUMBER	TEST NUMBER
23-015	067

UN DRUM QUALIFICATION TEST REPORT

- PERIODIC RE-TESTING -

Qualification Testing and Periodic Retesting for steel drums is performed in accordance with applicable sections of the following:
U.N. Recommendations on the Transport of Dangerous Goods, 49 CFR §173.22 and .24, §178.2, §178.600 through §178.606 and .608
 in addition to Skolnik Industries, Inc. Procedure SOP - 11.1.

U.N. MARKING:

1A2/X220/S

PART NUMBER:

CQ2006Q**HM2001Q**

TEST DATE:

(Periodic Retesting is required within 12 months from test date)

March 10, 2023

DRUM DESCRIPTION

DRUM TYPE:	Open Head	ROLLING HOOPS:	Two
MATERIAL:	Carbon Steel	RING:	Leverlock RQ2013
THICKNESS: (top/body/bottom)	1.2 / 1.2 / 1.2 mm	NUT/BOLT TYPE:	N/A
CAPACITY:	20 Gallon	CLOSING INSTRUCTIONS:	PQ 080 Rev. F
INSIDE DIAMETER:	18.25"	GASKET:	"D" EPDM GE2000
OVERALL HEIGHT:	21.5"	CHIME TYPE:	Round Chime
PACKAGING GROUP:	I Solids	SEAM CONSTRUCTION:	Overlap Weld
SPECIFIC GRAVITY:	1.5	FITTINGS:	2" & 3/4" Rieke in Cover PR2041 PR3041 EPDM Gasket
SOLIDS GROSS WEIGHT:	220 kg	DRUM TARE WEIGHT:	13 Kg
MAXIMUM CAPACITY:	21.1 Gallon		

TESTING

DROP TEST - SOLIDS

49 CFR §178.603

CONTENTS USED:	Sand and Steel Plates
CAPACITY FILLED TO:	95%
SOLID DROP HEIGHT:	1.8 m
RESULTS, TEST 1:	PASS 3 samples dropped on bottom chime
RESULTS, TEST 2:	PASS 3 samples dropped onto ring at 45 degrees

DROP TEST - LIQUIDS

49 CFR §178.603

CONTENTS USED:	N/A
CAPACITY FILLED TO:	N/A
LIQUID DROP HEIGHT:	N/A
RESULTS, TEST 1:	N/A
RESULTS, TEST 2:	N/A

STACKING TEST - SOLIDS

49 CFR §178.606

CONTENTS USED:	Sand and Steel Plates
CAPACITY FILLED TO:	95%
TEST WEIGHT:	1659 kg 3 samples maintained for 24 hours
RESULTS:	PASS

STACKING TEST - LIQUIDS

49 CFR §178.606

CONTENTS USED:	N/A
CAPACITY FILLED TO:	N/A
TEST WEIGHT:	N/A
RESULTS:	N/A

LEAKPROOFNESS TEST

49 CFR §178.604

TEST PRESSURE:	34.5 kPa 3 samples held for (5) minutes
RESULTS:	PASS

VIBRATION STANDARD

49 CFR §178.608


The vibration standard criteria as set forth in 49 CFR § 178.608 was successfully reviewed upon design qualification testing for this type of container. Past performance has indicated no failures.

HYDROSTATIC TEST

49 CFR §178.605

TEST PRESSURE:	N/A
RESULTS:	N/A

TEST PERSONNEL



Moises Basilio
 Inspection and Testing Manager

APPROVAL



Mike McKinley
 Director of Quality Assurance